PicAS® II EBS-1600

NEXT GENERATION

PROVEN TECHNOLOGY - MODERN DESIGN





131459 EBS-1600 PicAS II EN.indd 1 8/28/24 3:50 PM

A New Design of EBS' Proven Technology

The EBS-1600 is the latest generation of DOD products to come off the EBS drawing board. A modern cartridge system, along with a compact design provide a highly functional, easy-to-use printer.

No external compressed air is required, and annoying ink lines and cables are a thing of the past. In less than 10 minutes, the PicAS® II is installed and ready to run production. The latest cartridge technology makes changing consumables a clean affair: no drips, no mess, no tools!

Easy-To-Use Operating System

With the intuitive menu navigation you'll quickly find your way around the 10.1" color LCD touchscreen. Menu items can be customized.





so everything YOU need is always in view. In addition, individual profiles can be set up, allowing your personnel to be authorized for specific tasks. From switching the printer on and off, to complete control of all functions, everything can be assigned on a personnel-specific basis.

One Printer - Multiple Configurations

Three printhead configurations allow print heights from 6-58 mm. Narrow nozzle spacing for precise print, or larger nozzle spacing for additional print height, there are lots of possibilities!

131459 EBS-1600 PicAS II EN.indd 2 8/28/24 3:50 PM

Specifications

Technical data		
Maximum print height	29 mm (1,14") - Printhead 16N/29 56 mm (2,20") - Printhead 16N/56 58 mm (2,28") - Printhead 32N/58 Adjustment of print height and vertical resolution: yes, by slanting the printhead	
Maximum print speed (at non slanted printhead)	Up to 100 m/min (at a horizontal resolution not higher than 550 dots/m) for printheads 16N/29, 32N/58 Up to 200 m/min (at a horizontal resolution not higher than 275 dots/m) for printheads 16N/56	
Integrated printhead	Number of Printheads: Types of printheads: Number of degrees to slant: Nozzle diameter and spacing:	1 16N/29, 16N/56, 32N/58 5 150 µm/1,8 mm for printheads 7N/13, 16N/29, 32N/58 170 µm/3,6 mm for printheads 7N/24, 16N/56
Ingress protection rate	Control unit: Integrated printhead:	IP54 IP55
Working position of printhead	any	
Operational control	10.1" TFT color display with touch function	
Memory capacity	1 GB	
Objects	Text objects/codes: static texts, date/time, calendar, working shift code, counter, text file, communication ports, graphic objects (line, rectangle, ellipsis, picture)	
Fonts	Font types: Matrix, TrueType possible installation of additional fonts in format: *.ttf, *.bdf, *.pcf	
Barcode/Matrix codes	1D-Codes: GS1-Data Bar 14, GS1 Data Bar Limited, GS1 Data Bar Expanded 2D-Codes: QR-Code, Data Matrix ECC200	
External interface	Ethernet, USB-Port	
Ink base	Ethanol, Acetone or MEK	
Print timing	Internal generator or external shaft encoder (optional)	
Cartridge content	approx. 500 ml or approx. 1,000 ml	
Power supply	100-240 V ~ 50/60 Hz	
Weight	complete printer incl. 1,000 ml ink: approx. 7.6 kg	

131459 EBS-1600 PicAS II EN.indd 3 8/28/24 3:50 PM

Depend on the EBS Group

EBS Ink-Jet Systems has been providing leadingedge solutions for contact-free coding since 1977.

Today the EBS Group consists of four primary companies located in Germany, Poland, China, and the United States. In addition, we maintain several subventures and numerous cooperative partnerships.

We engineer, develop and produce our own systems. The EBS Group sales network consists of over 120 distributors, dealers and OEMs in more than 60 countries. All share these common goals:

- Superior quality
- Outstanding service
- · High-quality products
- Fair pricing
- Total customer satisfaction



SALES, LOGISTICS & TECHNICAL SUPPORT

IISA

EBS Ink-Jet Systems USA, Inc. 1840 Industrial Drive - Suite 200 Libertyville, IL 60048

Tel: (001) 847 996 0739

Fax: (001) 847 996 0843

E-Mail: america@ebs-inkjet.com

www.ebs-inkjet-usa.com



CHINA

EBS Ink-Jet Systems
(SHENZHEN) Co., Ltd.
Unit 608, Building Jin-Hui-Qiu No.5,
Langshan 2nd Road, Gaoxin bei qu,
Nanshan District
518057 Shenzhen China
Tel: (+86) 755 2340 0676
Fax:(+86) 755 2340 0376
E-Mail: office@ebs-china.com



PRODUCTION & DEVELOPMENT

HEADQUARTERS GERMANY

www.ebs-inkjet-china.com

EBS Ink Jet Systeme GmbH Alte Ziegelei 19–25 51588 Nümbrecht-Elsenroth Deutschland

Tel: 02293 / 939-0 Fax: 02293 / 939-3 E-Mail: mail@ebs-inkjet.de www.ebs-inkjet.de



POLAND

EBS Ink-Jet Systems Poland Sp.z o.o. ul. Tarnogajska 13

50-512 Wroclaw (Breslau)

Polen

Tel: (+48) 7136 70411 Fax: (+48) 7137 33 269 E-Mail: office@ebs-inkjet.pl www.ebs-inkjet.pl

Distributor:



EBS Ink-Jet Systems USA, Inc. 1840 Industrial Drive, Suite 200 Libertyville, IL 60048 Phone: 1-847-996-0739 Email: sales@ebs-inkjet.com www.ebs-inkjet-usa.com

Printed in U.S.A. February 2024

131459 EBS-1600 PicAS II EN.indd 4 8/28/24 3:50 PM